



ARIAL 4T MOTORCYCLE SAE 10W-40



This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

SKU: 502010

Categories: [4-тактови моторни масла](#)

A new generation semi-synthetic engine oil for four-stroke motorcycles formulated with high quality mineral and synthetic base oils combined with special developed balanced additives to achieve the following properties:

- a high and stable viscosity index
- good cold start properties
- optimal friction characteristics
- a very strong protection against wear, corrosion and foaming
- a very good detergency and dispersion

Application:

This oil is special developed for the lubrication of four-stroke motorcycles, so that sliding, sticking and/or rough changing of the clutch-plates no longer occurs. This oil is developed and tested in co-operation with the most important motorcycle producers and has its performance demonstrated in the field.

Performance Level:

API SL
JASO MA2
JASO MA

Typicals:

Density at 15 °C, kg/l: 0,871

Viscosity -25 °C, mPa.s: 4050

Viscosity 40 °C, mm²/s: 87,00Viscosity 100 °C, mm²/s: 13,80

Viscosity Index: 163

Flash Point COC, °C: 210

Pour Point, °C: -30

Total Base Number, mgKOH/g: 7,7

Sulphate Ash, %: 0,94

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.