

## ARIAL ATF 289



This fluid may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required.

---

**SKU:** 302010

**Categories:** [Течности за автоматични скоростни кутии](#)

A very high graded automatic transmission fluid formulated with solvent refined base oils and a number of selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

### **Application:**

This fluid may be used for automatic gearboxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID fluid is required.

### **Performance Level:**

Allison C4  
Cat TO-2  
Ford Mercon/M2C138-CJ/166-H  
GM Dexron IID  
MAN 339 Typ Z1/V1  
MB 236.6/236.7  
Voith 55.6335 (G607)

ZF TE-ML 09/11A/14A

**Typicals:**

Density at 15 °C, kg/l: 0,857

Viscosity 40 °C, mm<sup>2</sup>/s: 43,20Viscosity 100 °C, mm<sup>2</sup>/s: 8,25

Viscosity Index: 168

Flash Point COC, °C: 198

Pour Point, °C: -45

Total Base Number, mgKOH/g: 1,5

Sulphate Ash, %: 0,18

**Packaging:**

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.