

ARIAL G-LiFe SAE 85W-90



High performance gearbox oil for axle gears subjected to high loads in passenger cars, heavy-goods vehicles, buses, as well as construction and agricultural machinery.

SKU: 301040

Categories: [Течности за ръчни скоростни кутии](#)

PRODUCT DESCRIPTION

ARIAL G-LiFe SAE 85W-90 is a high-performance gearbox oil of SAE grade 85W-90 produced using selected base oils with exceptional wear protection properties.

Application:

ARIAL G-LiFe SAE 85W-90 is used for axle gears in passenger cars, heavy-goods vehicles and buses as well as construction and agricultural machinery in accordance with the manufacturer's specifications and provides the highest level of wear protection here.

Performance Level:

API GL-5
MIL-L-2105D

Meets the requirements of
MB 235.0
ZF TE-ML 07A/16B/17B/19B/21A
MAN 342 Typ M1

Benefits:

Excellent wear protection
Very good load carrying capacity under heavy continuous loads
Extremely stable to shear stress - 'Stay-in-grade' Stable lubricating film, even with very hot oil and under very high loads, and safe wear protection
Good noise reduction

Good lubrication and lower 'cold wear' Outstanding corrosion protection

Good seal compatibility

Low tendency to foam, even at high speeds

Miscible and compatible with other gearbox oils. However, in order to exploit the full product benefits of ARIAL G-LiFe SAE 85W-90a complete oil change is recommended.

Typicals:

Density at 15 °C, kg/l: 0,898

Viscosity 40 °C, mm²/s: 199,00

Viscosity 100 °C, mm²/s: 17,80

Viscosity Index: 97

Flash Point COC, °C: 230

Pour Point, °C: -18

Packaging:

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.