



ARIAL TWO STROKE ASHLESS



This two-stroke motor oil is advised for all outboard engines and is used in a ratio of 1 part of oil to 50 parts of gasoline. Other mixing ratios are also possible, it is recommended to adhere to the mixing ratio prescribed by the manufacturer.

SKU: 601010

Categories: [2-тактови масла за моторни лодки](#)

PRODUCT DESCRIPTION

A two stroke engine oil formulated with carefully selected high quality base oils and special ashless two stroke additives to achieve the following properties:

- a perfect lubrication of all motor parts
- a powerful detergency and activity against wear and corrosion
- a limited formation of smoke

Application:

This two-stroke motor oil is advised for all outboard engines and is used in a ratio of 1 part of oil to 50 parts of gasoline. Other mixing ratios are also possible, it is recommended to adhere to the mixing ratio prescribed by the manufacturer.

Performance Level:

NMMA TC-W3

Typicals:

Density at 15 °C, kg/l: 0,873

Viscosity 40 °C, mm²/s: 35,60

Viscosity 100 °C, mm²/s: 6,29

Viscosity Index: 126

Flash Point PM, °C: 107

Pour Point, °C: -30

Total Base Number, mgKOH/g: 8,7

Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.