



## ARIAL TWO STROKE ASHLESS



This two-stroke motor oil is advised for all outboard engines and is used in a ratio of 1 part of oil to 50 parts of gasoline. Other mixing ratios are also possible, it is recommended to adhere to the mixing ratio prescribed by the manufacturer.

---

**SKU:** 601010

**Categories:** [2-тактови масла за моторни лодки](#)

A two stroke engine oil formulated with carefully selected high quality base oils and special ashless two stroke additives to achieve the following properties:

- a perfect lubrication of all motor parts
- a powerful detergency and activity against wear and corrosion
- a limited formation of smoke

### **Application:**

This two-stroke motor oil is advised for all outboard engines and is used in a ratio of 1 part of oil to 50 parts of gasoline. Other mixing ratios are also possible, it is recommended to adhere to the mixing ratio prescribed by the manufacturer.

### **Performance Level:**

NMMA TC-W3

### **Typicals:**

Density at 15 °C, kg/l: 0,873

Viscosity 40 °C, mm<sup>2</sup>/s: 35,60

Viscosity 100 °C, mm<sup>2</sup>/s: 6,29

Viscosity Index: 126

Flash Point PM, °C: 107

Pour Point, °C: -30

Total Base Number, mgKOH/g: 8,7

**Packaging:**

	<b>litres</b>	<b>packing</b>	<b>per box</b>	<b>per pallet</b>
1		canister	12	*600
5		canister	4	*120
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.