



ARIAL UTTO HYDRAULIC 540



This very high quality universal tractor transmission oil (UTTO) has been developed for heavy loaded hydraulics and transmissions, with or without wet brakes, of agricultural and road-construction equipment. This oil can also be used in certain continuously variable transmissions (CVT) of agricultural and road-construction equipment.

SKU: N/A

Categories: [Многофункционални масла \(UTTO\)](#)

PRODUCT DESCRIPTION

A very high quality universal hydraulic and transmission oil formulated with high quality base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a high thermal stability
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

Application:

This very high quality universal tractor transmission oil (UTTO) has been developed for heavy loaded hydraulics and transmissions, with or without wet brakes, of agricultural and road-construction equipment. This oil can also be used in certain continuously variable transmissions (CVT) of agricultural and road-construction equipment.

Performance Level:

API GL-4
Allison C4
Cat TO-2
Case MS 1210
CNH MAT 3540/3525
FNHA-2-C-200.00/201.00
Ford M2C86-C/M2C134-D
John Deere J20C/D
Massey Ferguson M1141/M1143/M1145
Valtra G2-08
Volvo WB 101
ZF TE-ML 03E/05F/06K/17E/21F

Typicals:

Density at 15 °C, kg/l: 0,867
Viscosity 40 °C, mm²/s: 60,00
Viscosity 100 °C, mm²/s: 9,30
Viscosity Index: 136
Flash Point COC, °C: 215
Pour Point, °C: -45
Total Base Number, mgKOH/g: 9,9
Sulphate Ash, %: 1,49

Packaging:

litres	packing		per box	per pallet
20	canister	-		24
60	barrel	-		9
208	barrel	-		4
1000	pallet tank	-		1

*CP pallet size 114 x 114 cm.