



ARIAL UTTO WB HT



This very high-quality universal tractor transmission oil (UTTO) has been developed for the heavy loaded hydraulics and transmissions, with or without wet brakes, of most generally used agricultural and roadconstruction equipment.

SKU: 201050 Categories: <u>Многофункционални масла</u> (<u>UTTO)</u>

A very high quality universal hydraulic and transmission oil formulated with unconventional base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a high thermal stability
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

Application:

This very high-quality universal tractor transmission oil (UTTO) has been developed for the heavy loaded hydraulics and transmissions, with or without wet brakes, of most generally used agricultural and road-construction equipment.

Performance Level:

API GL-4 Allison C4 Case MS1207/MS1209 Cat TO-2



John Deere J20A Massey Ferguson M1141/M1143/M1145 Volvo WB 102 ZF TE-ML 03E/05F/06K

Typicals:

Density at 15 °C, kg/l: 0,856 Viscosity 40 °C, mm²/s: 39,30 Viscosity 100 °C, mm²/s: 7,70 Viscosity Index: 170 Flash Point COC, °C: 224 Pour Point, °C: -42

Packaging:

litres	packing	per box	per pallet
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1
*CP pallet size 114 x 114 cm.			