

ARIAL ATF 15 LVB



This premium synthetic product is specially formulated for the lubrication of the latest generation of automatic 7G-Tronic Plus transmissions from Mercedes-Benz for which an oil with the specification MB 236.15 is required. This oil contributes considerably to the realization of fuel saving.

Artikelnummer: 302070

Kategorien: [Automatik-Getriebeöle](#)

A very high graded, very low viscosity automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- important contribution fuel economy
- excellent lubrication
- very good resistance against oxidation and a very high thermal stability
- excellent and very stable friction characteristics that enable longer oil-replacement intervals
- excellent resistance against foaming
- excellent protection against wear
- a very high and stable viscosity index
- dark blue coloured

Application:

This premium synthetic product is specially formulated for the lubrication of the latest generation of automatic 7G-Tronic Plus transmissions from Mercedes-Benz for which an oil with the specification MB 236.15 is required. This oil contributes considerably to the realization of fuel saving.

Performance Level:

MB 236.15

Typicals:

Density at 15 °C, kg/l: 0,835

Viscosity 40 °C, mm²/s: 18,80

Viscosity 100 °C, mm²/s: 4,40

Viscosity Index: 150

Flash Point COC, °C: 188

Pour Point, °C: -57

Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.