



## ARIAL FS 2T AIR COOLED



This two-stroke engine oil is specially suitable for the lubrication of high speed two stroke engines under heavy duty load. This self-mixing two stroke engine oil is also advised for use in two stroke scooters, on which often radiator coolers are fitted.

---

**Artikelnummer:** 501020

**Kategorien:** [2-Takt-Motorenöle](#)

## BESCHREIBUNG

A full-synthetic two stroke engine oil formulated with carefully selected high quality synthetic base oils (ester) and special two stroke additives to achieve the following properties:

- a perfect lubrication of all motor parts
- a very active detergency, preventing from deposits in the combustion zone and at the scavenger ports
- preventing spark plugs from fouling, in this way securing an optimal output of the engine
- a very strong activity against wear and corrosion
- a very limited formation of smoke
- self-mixing

### **Application:**

This two-stroke engine oil is specially suitable for the lubrication of high speed two stroke engines under heavy duty load. This self-mixing two stroke engine oil is also advised for use in two stroke scooters, on which often radiator coolers are fitted.

### **Performance Level:**

API TC  
JASO FD  
Husqvarna

ISO-L-EGD  
Piaggio Hexagon

**Typicals:**

Density at 15 °C, kg/l: 0,880  
Viscosity 40 °C, mm<sup>2</sup>/s: 70,50  
Viscosity 100 °C, mm<sup>2</sup>/s: 11,00  
Viscosity Index: 147  
Flash Point PM, °C: 78  
Pour Point, °C: -45  
Total Base Number, mgKOH/g: 2,9  
Sulphate Ash, %: 0,12

**Packaging:**

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.