



ARIAL STOU 10W-30



An up-to-date multifunctional lubricating oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined base oils and additives

Artikelnummer: 203020

Kategorien: [Supertraktoröl Universal \(STOU\)](#)

BESCHREIBUNG

An up-to-date multifunctional lubricating oil for agricultural and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to achieve the following properties:

- a powerful dispersion and detergency
- a high activity against wear, corrosion and foam
- a very strong resistance to oxidation
- an excellent extreme pressure properties
- a high and stable viscosity index

Application:

This multifunctional lubricant * has been developed to achieve one single lubricating oil that is able to lubricate:

- gasoline engines
- diesel engines (with or without turbo-charging)
- transmissions (also "wet" brakes)
- hydraulic systems

* a so-called Super Tractor Oil Universal = STOU

Performance Level:

API SF/CG-4/GL-4

ACEA E3, MIL-L-2104D
Ford M2C159-C
John Deere J27
Massey Ferguson CMS M1139/M1144/M1145
MB 227.1
ZF TE-ML 06B/07B
Allison C4
Cat TO-2
Ford M2C134-D
John Deere J20C
Massey Ferguson CMS M1135/M1143
NH 410B

Typicals:

Density at 15 °C, kg/l: 0,877
Viscosity -25 °C, mPa.s: 4730
Viscosity 40 °C, mm²/s: 70,60
Viscosity 100 °C, mm²/s: 11,40
Viscosity Index: 154
Flash Point COC, °C: 228
Pour Point, °C: -33
Total Base Number, mgKOH/g: 11,3
Sulphate Ash, %: 1,57

Packaging:

| litres | packing | | per box | per pallet |
|--------|-------------|---|---------|------------|
| 20 | canister | - | | 24 |
| 60 | barrel | - | | 9 |
| 208 | barrel | - | | 4 |
| 1000 | pallet tank | - | | 1 |

*CP pallet size 114 x 114 cm.