



ARIAL TWO STROKE HS



This two-stroke engine oil is advised for the lubrication of high-speed air cooled two stroke engines under heavy duty load. This self-mixing two stroke engine oil may also be used for water cooled two stroke engines (radiator type cooling systems).

Artikelnummer: 501010

Kategorien: [2-Takt-Motorenöle](#)

BESCHREIBUNG

A two stroke engine oil formulated with carefully selected high quality mineral and synthetic base oils and special two stroke additives to achieve the following properties:

- a perfect lubrication of all motor parts
- an active detergency, preventing from deposits in the combustion zone and at the scavenger ports
- preventing spark plugs from fouling, in this way securing an optimal output of the engine
- a very effective activity against wear and corrosion
- a very limited formation of smoke
- self mixing

Application:

This two-stroke engine oil is advised for the lubrication of high-speed air cooled two stroke engines under heavy duty load. This self-mixing two stroke engine oil may also be used for water cooled two stroke engines (radiator type cooling systems).

Performance Level:

API TC
JASO FD
Global GD
Husqvarna 272

ISO-L-EGD
2-Stroke DFI

Typicals:

Density at 15 °C, kg/l: 0,871
Viscosity 40 °C, mm²/s: 64,60
Viscosity 100 °C, mm²/s: 9,50
Viscosity Index: 129
Flash Point COC, °C: 116
Pour Point, °C: -24
Total Base Number, mgKOH/g: 1,4
Sulphate Ash, %: 0,14

Packaging:

| | litres | packing | per box | per pallet |
|------|--------|-------------|---------|------------|
| 1 | | canister | 12 | *600 |
| 5 | | canister | 4 | *120 |
| 60 | | barrel | - | 9 |
| 208 | | barrel | - | 4 |
| 1000 | | pallet tank | - | 1 |

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.