



ARIAL UTTO HYDRAULIC



This universal tractor transmission oil (UTTO) has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment.

Artikelnummer: 201040

Kategorien: [Multifunktionsöle \(UTTO\)](#)

BESCHREIBUNG

A nowadays universal hydraulic and transmission oil formulated with solvent refined base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefore applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

Application:

This universal tractor transmission oil (UTTO) has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment.

Performance Level:

API GL-4

Allison C4

Case MS1206/MS1207/MS1209

Cat TO-2

CNH MAT 3525

Ford M2C134-D
John Deere J20C
Massey Ferguson M1141/M1143
Volvo WB 101
ZF TE-ML 03E/05F/06K

Typicals:

Density at 15 °C, kg/l: 0,885
Viscosity 40 °C, mm²/s: 52,00
Viscosity 100 °C, mm²/s: 9,15
Viscosity Index: 156
Flash Point COC, °C: 244
Pour Point, °C: -39
Total Base Number, mgKOH/g: 7,3
Sulphate Ash, %: 1,19

Packaging:

litres	packing		per box	per pallet
20	canister	-		24
60	barrel	-		9
208	barrel	-		4
1000	pallet tank	-		1

*CP pallet size 114 x 114 cm.