



## ARIAL UTTO WB HT



This very high-quality universal tractor transmission oil (UTTO) has been developed for the heavy loaded hydraulics and transmissions, with or without wet brakes, of most generally used agricultural and road-construction equipment.

---

**Artikelnummer:** 201050

**Kategorien:** [Multifunktionsöle \(UTTO\)](#)

A very high quality universal hydraulic and transmission oil formulated with unconventional base oils and selected additives to obtain the following properties:

- a high and stable viscosity index
- a very low pour point
- a very good stability against oxidation
- a high thermal stability
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties

### **Application:**

This very high-quality universal tractor transmission oil (UTTO) has been developed for the heavy loaded hydraulics and transmissions, with or without wet brakes, of most generally used agricultural and road-construction equipment.

### **Performance Level:**

API GL-4  
Allison C4  
Case MS1207/MS1209  
Cat TO-2

John Deere J20A  
Massey Ferguson M1141/M1143/M1145  
Volvo WB 102  
ZF TE-ML 03E/05F/06K

**Typicals:**

Density at 15 °C, kg/l: 0,856  
Viscosity 40 °C, mm<sup>2</sup>/s: 39,30  
Viscosity 100 °C, mm<sup>2</sup>/s: 7,70  
Viscosity Index: 170  
Flash Point COC, °C: 224  
Pour Point, °C: -42

**Packaging:**

litres	packing		per box	per pallet
20	canister	-		24
60	barrel	-		9
208	barrel	-		4
1000	pallet tank	-		1

\*CP pallet size 114 x 114 cm.