

ARIAL 2T RACING



This selfmixing two stroke engine oil is special advised for the lubrication of high speed two stroke engines under heavy duty load and specially suitable for use in kart- and racing motors.

SKU: 104070

Categories: [Engine oil for racing cars](#)

PRODUCT DESCRIPTION

A full synthetic two stroke engine oil, formulated with carefully selected high quality synthetic base oils (ester) and special two stroke additives to achieve the following properties:

- a perfect lubrication of all motor parts
- a very active detergency, preventing from deposits in the combustion zone and at the scavenger ports
- preventing spark plugs from fouling, in this way securing an optimal output of the engine
- a very strong activity against wear and corrosion.
- a very limited formation of smoke
- self-mixing

Application:

This selfmixing two stroke engine oil is special advised for the lubrication of high speed two stroke engines under heavy duty load and specially suitable for us in kart- and racing motors.

Performance Level:

API TC
JASO FD
Husqvarna
ISO-L-EGD
Piaggio Hexagon

Typicals:

Density at 15 °C, kg/l: 0,880
Viscosity 40 °C, mm²/s: 44,00
Viscosity 100 °C, mm²/s: 8,80
Viscosity Index: 185
Flash Point PM, °C: 78
Pour Point, °C: -48
Total Base Number, mgKOH/g: 6,6
Sulphate Ash, %: 0,26

Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.