

## ARIAL ATF 7G



This fluid may be used for automatic transmissions of different car manufacturers.

---

**SKU:** 302040

**Categories:** [Automatic transmission fluids](#)

## PRODUCT DESCRIPTION

A very high graded automatic transmission fluid formulated with a number of special selected base oils and additives to obtain the following properties:

- a high shifting comfort
- a very low pour point
- very good stability against oxidation
- very good thermal properties
- a positive activity against wear, corrosion and foam
- a constant friction stability over lifetime ensuring perfect clutch operation
- a perfect compatibility with seals and non-ferro metals
- extremely resistant against shudder vibration
- as a result of the perfect viscosity grade a fuel-efficiency potential
- red coloured

### Application:

This fluid may be used for automatic transmissions of different car manufacturers.

### Performance Level:

- Allison C4/TES-389
- Chrysler ATF++/2/+3/+4
- Ford Mercon V/Mercon/WSS-M2C922-A1
- GM Dexron II/IID/IIIE/IIIG/IIIH
- Honda ATF-Z1 (except in CVT)

Hyundai/Kia SP-II/SP-III  
Isuzu ATF II/III  
Jaguar JLM 20238/20292/21044  
JASO M315 Type 1A  
Mazda M-III/Type T-IV  
MB 236.3/236.5/236.6/236.7/236.8  
MB 236.9/236.10/236.11/236.91  
Mitsubishi SP-II/SP-III/ATF J-2  
Nissan Matic D/J/K/W  
Subaru ATF HP, Suzuki ATF 3314/3317  
Toyota Type DII/T/T-III/T-IV  
VAG G-052-025/052-055/052-162/052-990/055-025  
Volvo 1161540, ZF TE-ML 11A/11B

**Typicals:**

Density at 15 °C, kg/l: 0,855  
Viscosity -30 °C, mPa.s: 2980  
Viscosity 40 °C, mm<sup>2</sup>/s: 33,10  
Viscosity 100 °C, mm<sup>2</sup>/s: 7,10  
Viscosity Index: 185  
Flash Point COC, °C: 200  
Pour Point, °C: -54

**Packaging:**

litres	packing	per box	per pallet
1	canister	12	*600
5	canister	4	*120
20	canister	-	24
60	barrel	-	9
208	barrel	-	4
1000	pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.