

## ARIAL ATF DMM



This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIHH fluid is required.

---

**SKU:** 302020

**Categories:** [Automatic transmission fluids](#)

## PRODUCT DESCRIPTION

A very high graded automatic transmission fluid formulated with solvent refined and synthetic base oils and a number of selected additives to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- very good stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties
- a perfect compatibility with seals and non-ferro metals
- red coloured

### Application:

This fluid may be used for automatic gear boxes, power steering units, torque converters and other equipment, for which an ATF Dexron IID, IIE, IIIF, IIIG or IIHH fluid is required.

### Performance Level:

Allison C4/TES-389  
Cat TO-2  
Ford Mercon/M2C138-CJ/166-H  
GM Dexron IID/IIE/IIIF/IIIG/IIHH  
MAN 339 Typ Z1/V1  
MB 236.1/236.5/236.6/236.7/236.9  
Voith 55.6335 (G607)

Volvo 97341  
ZF TE-ML 02F/03D/04D/09A/09B/11A/11B/14A/17C

**Typicals:**

Density at 15 °C, kg/l: 0,851  
Viscosity 40 °C, mm<sup>2</sup>/s: 37,70  
Viscosity 100 °C, mm<sup>2</sup>/s: 7,60  
Viscosity Index: 175  
Flash Point COC, °C: 210  
Pour Point, °C: -51

**Packaging:**

	<b>litres</b>	<b>packing</b>	<b>per box</b>	<b>per pallet</b>
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.