

## ARIAL ATF WS ASIA



This fluid may be used for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications. It is recommended to follow the instructions of the manufacturer.

---

**SKU:** 302080

**Categories:** [Automatic transmission fluids](#)

## PRODUCT DESCRIPTION

A synthetic automatic transmission fluid, based on synthetic base oils, formulated with special friction modifiers to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- an excellent stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties and consequently low noise and smooth switching
- compatible with synthetic seals
- a quick oil provision at cold start conditions
- without dye

### Application:

This fluid may be used for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications. It is recommended to follow the instructions of the manufacturer.

### Performance Level:

Aisin Warner JWS 3309/3324  
Allison C4/TES-228  
BMW 7045E/8072B  
Chrysler ATF+3/ATF+4  
Ford Mercon/M2C 138CJ/166H/922-A1/924-A  
GM Dexron IID/IIIE/IIIG/IIIH, TASA

Honda ATF-Z1 (except in CVT)  
Hyundai/Kia SP-II/SP-III  
Isuzu Besco ATF II/III  
JASO M 315-2013 Type 1A  
Mazda ATF M-V  
MB 236.1/236.6/236.7/236.8/236.9/236.10  
Nissan Matic Fluid C/D/J/K  
Subaru ATF/ATF 5AT/ATF HP/Dexron II  
Suzuki ATF 3314  
Toyota ATF T-III/T-IV/D-II/WS  
VAG G-055-025  
Volvo 1161540  
ZF TE-ML 09/11A/11B

**Typicals:**

Density at 15 °C, kg/l: 0,88  
Viscosity 40 °C, mm<sup>2</sup>/s: 36,0  
Viscosity 100 °C, mm<sup>2</sup>/s: 7,20  
Viscosity Index: 165  
Flash Point COC, °C: 212  
Pour Point, °C: -45  
Total Base Number, mgKOH/g: 2,7

**Packaging:**

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

\*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.