



ARIAL EXTLIFE SAE 0W-40 RS



A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

SKU: 10105

Categories: [Engine oils for passenger cars](#)

A modern, synthetic, universal motor oil based on special selected synthetic base oils with a high viscosity index and a well balanced choice of advanced additives to obtain the following properties:

- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a very strong resistance against oxidation
- a safe lubrication film at very high temperatures
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

Application:

A universal, special composed synthetic motor oil recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans for which the most modern specifications are required.

Performance Level:

ACEA A3/B4

API SN/CF

BMW Longlife-01

MB 229.3/226.5

Porsche A40

Renault RN0700/RN0710

VW 502.00/505.00

Typicals:

Density at 15 °C, kg/l: 0,844

Viscosity -35 °C, mPa.s: 5620

Viscosity 40 °C, mm²/s: 75,90Viscosity 100 °C, mm²/s: 13,50

Viscosity Index: 183

Flash Point COC, °C: 238

Pour Point, °C: -48

Total Base Number, mgKOH/g: 10,3

Sulphate Ash, %: 1,33

Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.