



ARIAL EXTLIFE SAE 5W-30 FO



This fuel economy motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below. This motor oil is specially developed for those cars, that ask for motor oils that fulfill the requirements of the Ford M2C913-A and Ford M2C913-B.

SKU: 10109

Categories: [Engine oils for passenger cars](#)

PRODUCT DESCRIPTION

This semi-synthetic fuel economy motor oil is produced with special selected mineral and synthetic base oils and a well-balanced choice of advanced additives to obtain the following properties:

- a lower fuel consumption
- a high and stable viscosity index
- a high resistance against shearing
- a fast cold start
- a strong resistance against oxidation
- a safe lubrication film at high temperatures
- a good detergency and dispersion power
- a strong protection against wear, corrosion and foaming

Application:

This fuel economy motor oil is recommended for use in petrol- and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with the specifications as stated below. This motor oil is specially developed for those cars, that ask for motor oils that fulfill the requirements of the Ford M2C913-A and Ford M2C913-B.

Performance Level:

ACEA A5/B5

API SL/CF
Ford WSS-M2C913-A/B

Typicals:

Density at 15 °C, kg/l: 0,851
Viscosity -30 °C, mPa.s: 4600
Viscosity 40 °C, mm²/s: 55,30
Viscosity 100 °C, mm²/s: 9,77
Viscosity Index: 164
Flash Point COC, °C: 230
Pour Point, °C: -39
Total Base Number, mgKOH/g: 8,6
Sulphate Ash, %: 1,11

Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.