



ARIAL RACING SAE 10W-30



A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

SKU: 104040

Categories: [Engine oil for racing cars](#)

PRODUCT DESCRIPTION

A fully synthetic engine oil based on carefully selected high quality synthetic base oils, among others ester, all of which already have a natural, high viscosity index and which advanced and well balanced additives in order to obtain the following properties:

- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

Application:

A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

Performance Level:

ACEA A3/B4

API SH/CF

API SN/CF*

* API SN quality only;

not-licensable due to phosphorus-limit.

Typicals:

Density at 15 °C, kg/l: 0,878

Viscosity -25 °C, mPa.s: 2730

Viscosity 40 °C, mm²/s: 71,68Viscosity 100 °C, mm²/s: 12,10

Viscosity Index: 167

Flash Point COC, °C: 230

Total Base Number, mgKOH/g: 10,3

Sulphate Ash, %: 1,33

Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.