



## ARIAL TRUCK RACING SAE 15W-60



A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.

---

**SKU:** 103060

**Categories:** [Engine oil for racing cars](#),  
[Engine oils for commercial vehicles](#)

## PRODUCT DESCRIPTION

A fully synthetic robust engine oil developed for use under extreme severe conditions. This product is specially designed for trucks that are used in "off-road races". Through the use of a special combination of synthetic base oils, among others ester and advanced additives has this product a very strong lubricant film. This engine oil has through its composition a high resistance to oxidation and viscosity loss under high load. This engine oil has the following typical properties:

- a very low tendency to evaporation
- a high and very stable viscosity index
- a good resistance against shearing
- a high resistance against aging
- a safe lubrication film at low and very high temperatures
- a very good detergency and dispersion power
- a very strong protection against wear, corrosion and foaming

### **Application:**

A fully synthetic engine oil, designed for cars for race conditions where the highest performance is required. This oil has proven its quality under the most extreme conditions particularly in races.



**Performance Level:**

ACEA E6, E7, E9

API CJ-4

**Typicals:**

Density at 15 °C, kg/l: 0,862

Viscosity -20 °C, mPa.s: 6430

Viscosity 40 °C, mm<sup>2</sup>/s: 166,00

Viscosity 100 °C, mm<sup>2</sup>/s: 22,90

Viscosity Index: 166

Flash Point COC, °C: 228

Pour Point, °C: -54

Total Base Number, mgKOH/g: 9,6

**Packaging:**

litres	packing	per box	per pallet
20	canister	-	24
208	barrel	-	4
1000	pallet tank	-	1

**litres****packing****per box****per pallet**

\*CP pallet size 114 x 114 cm.

