

ARIAL ATF 8G



This premium synthetic product is specially formulated for the lubrication of ZF 8HP transmissions. This oil contributes greatly to realizing fuel saving and can be used amongst others in the ZF 8HP transmissions 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions, which are used in various VAG models.

SKU: 302050

Categories: [Трансмиссионные масла для АКПП](#)

A very high graded automatic transmission fluid based on special selected synthetic base oils, with a high viscosity index and a number of selected additives to obtain the following properties:

- important contribution fuel economy
- excellent lubrication
- very good resistance against oxidation and a very high thermal stability
- excellent and very stable friction characteristics that enable longer oil-replacement intervals
- excellent resistance against foaming
- excellent protection against wear
- a very high and stable viscosity index
- green coloured

Application:

This premium synthetic product is specially formulated for the lubrication of ZF 8HP transmissions. This oil contributes greatly to realizing fuel saving and can be used amongst others in the ZF 8HP transmissions 8HP45, 8HP55, 8HP70 and 8HP90. It can also be used in certain ZF 6HP transmissions, which are used in various VAG models.

Performance Level:

BMW 8322 2152426/2289720(ATF3+)

Chrysler 68157995AA
Fiat 9.55550-AV5
Jaguar 02JDE 26444
Land Rover LR023288
VAG G-060-162

Typicals:

Density at 15 °C, kg/l: 0,842
Viscosity 40 °C, mm²/s: 25,80
Viscosity 100 °C, mm²/s: 6,00
Viscosity Index: 190
Flash Point COC, °C: 198
Pour Point, °C: -51

Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.