

ARIAL ATF WS ASIA



This fluid may be used for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications. It is recommended to follow the instructions of the manufacturer.

SKU: 302080

Categories: [Трансмиссионные масла для АКПП](#)

A synthetic automatic transmission fluid, based on synthetic base oils, formulated with special friction modifiers to obtain the following properties:

- a very high and stable viscosity index
- a very low pour point
- an excellent stability against oxidation
- a positive activity against wear, corrosion and foam
- specific friction properties and consequently low noise and smooth switching
- compatible with synthetic seals
- a quick oil provision at cold start conditions
- without dye

Application:

This fluid may be used for automatic transmissions, which are applied in several Japanese cars with before mentioned specifications. It is recommended to follow the instructions of the manufacturer.

Performance Level:

Aisin Warner JWS 3309/3324

Allison C4/TES-228

BMW 7045E/8072B

Chrysler ATF+3/ATF+4

Ford Mercon/M2C 138CJ/166H/922-A1/924-A

GM Dexron IID/IIIE/IIIG/IIIH, TASA

Honda ATF-Z1 (except in CVT)
Hyundai/Kia SP-II/SP-III
Isuzu Besco ATF II/III
JASO M 315-2013 Type 1A
Mazda ATF M-V
MB 236.1/236.6/236.7/236.8/236.9/236.10
Nissan Matic Fluid C/D/J/K
Subaru ATF/ATF 5AT/ATF HP/Dexron II
Suzuki ATF 3314
Toyota ATF T-III/T-IV/D-II/WS
VAG G-055-025
Volvo 1161540
ZF TE-ML 09/11A/11B

Typicals:

Density at 15 °C, kg/l: 0,88
Viscosity 40 °C, mm²/s: 36,0
Viscosity 100 °C, mm²/s: 7,20
Viscosity Index: 165
Flash Point COC, °C: 212
Pour Point, °C: -45
Total Base Number, mgKOH/g: 2,7

Packaging:

	litres	packing	per box	per pallet
1		canister	12	*600
5		canister	4	*120
20		canister	-	24
60		barrel	-	9
208		barrel	-	4
1000		pallet tank	-	1

*CP pallet size 114 x 114 cm. The number of boxes on a pallet may vary depending on the order.