



## ARIAL STOU 15W-40



An up-to-date multifunctional lubricating oil for agricultural- and earthmoving equipment, formulated with top-grade solvent refined base oils and additives

---

**SKU:** 203050

**Categories:** [Универсальные тракторные масла \(STOU\)](#)

## PRODUCT DESCRIPTION

An up-to-date multifunctional lubricating oil for agricultural- and earthmoving equipment, formulated with top-grade solvent refined base oils and additives, to achieve the following properties:

- a powerful dispersion and detergency
- a high activity against wear, corrosion and foam
- a very strong resistance to oxidation
- an excellent extreme pressure property
- a high and stable viscosity index

### Application:

This multifunctional lubricant \* has been developed to achieve one single lubricating oil that is able to lubricate:

- gasoline engines
- diesel engines (with or without turbo-charging)
- transmissions (also "wet" brakes)
- hydraulic systems

\* a so-called Super Tractor Oil Universal = STOU

### Performance Level:

API SF/CG-4/GL-4

ACEA E3, MIL-L-2104D  
John Deere J27  
Massey Ferguson CMS M1144/M1145  
MB 227.1  
ZF TE-ML 06B/07B  
Allison C4  
Cat TO-2  
Ford M2C134-D  
John Deere J20C  
Massey Ferguson CMS M1143

**Typicals:**

Density at 15 °C, kg/l: 0,884  
Viscosity -20 °C, mPa.s: 4760  
Viscosity 40 °C, mm<sup>2</sup>/s: 93,50  
Viscosity 100 °C, mm<sup>2</sup>/s: 14,50  
Viscosity Index: 137  
Flash Point COC, °C: 218  
Pour Point, °C: -36  
Total Base Number, mgKOH/g: 11,3  
Sulphate Ash, %: 1,57

**Packaging:**

litres	packing		per box	per pallet
20	canister	-		24
60	barrel	-		9
208	barrel	-		4
1000	pallet tank	-		1

\*CP pallet size 114 x 114 cm.