



## ARIAL UNILIFE SAE 10W-40 HC-T

лв. 1,270.53 с ДДС



This engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved.

**SKU:** 103030

**Categories:** [Моторные масла для грузового транспорта](#), [Моторные масла для смешанных автопарков](#)

## VARIATIONS

| Image   | SKU         | Price                 | Stock Status | Stock Quantity | Description Liters |
|---|-------------|-----------------------|--------------|----------------|--------------------|
|  | AR006104070 | лв. 1,270.53 с<br>ДДС |              |                | 208L               |

## PRODUCT DESCRIPTION

Low viscosity UHPD SAE 10W-40 engine oil based on HC synthetic base oils. Developed specifically for

diesel engines with an extended maintenance interval in heavy-goods vehicles, buses and work machines.

**Application:**

This engine lubricant is applicable to gasoline and diesel engines (normally- or turbo-aspirated) even under the toughest operation conditions and all the year round. This engine oil has a special additive system and may therefore be used, when fuels with relatively high sulphur contents are involved. This special quality of engine oil is mainly developed to allow extended oil drain intervals and to prevent "bore polishing" (=cylinder-wear) in diesel engines. This product is suitable for application in Euro 4 and Euro 5 engines.

**Performance Level:**

ACEA A3/B4, E7  
API CI-4/SL  
Cat ECF-1-a/ECF-2  
Cummins CES 20077/20078  
Detroit Diesel 93K215  
Deutz DQC III-10  
Global DHD-1  
JASO DH-1  
Mack EO-N  
MAN M 3275  
MB 228.3  
MTU Type 2  
Renault VI RLD-2  
Volvo VDS-3

**Typicals:**

Density at 15 °C, kg/l: 0,868  
Viscosity -25 °C, mPa.s: 4910  
Viscosity 40 °C, mm<sup>2</sup>/s: 87,70  
Viscosity 100 °C, mm<sup>2</sup>/s: 13,70  
Viscosity Index: 159  
Flash Point COC, °C: 222  
Pour Point, °C: -36  
Total Base Number, mgKOH/g: 11,1  
Sulphate Ash, %: 1,43

**Packaging:**

| litres | packing  |   | per box | per pallet |
|--------|----------|---|---------|------------|
| 20     | canister | - |         | 24         |
| 208    | barrel   | - |         | 4          |

| <b>litres</b> | <b>packing</b> | <b>per box</b> | <b>per pallet</b> |
|---------------|----------------|----------------|-------------------|
| 1000          | pallet tank    | -              | 1                 |

\*CP pallet size 114 x 114 cm.