



## ARIAL UNILIFE 15W-40 HD

лв. 1,254.57 с ДДС




This universal lubricating oil is suitable for gasoline or diesel engines, with or without super-charging. This motor oil is suitable for application in mixed fleets.

**SKU:** 103050

**Categories:** [Моторные масла для грузового транспорта](#), [Моторные масла для смешанных автопарков](#)

## VARIATIONS

Image	SKU	Price	Stock Status	Stock Quantity	Description Liters
	AR001154070	лв. 1,254.57 с ДДС			208L

A gasoline- and diesel engine oil, formulated with solvent refined base oils and a well-balanced choice of additives. This engine oil has the following properties:

- a very powerful detergency prevents deposits in the engine
- a very strong dispersion that prevents from precipitation and sludge
- a powerful activity against corrosion and foam
- a high and stable viscosity index

- a powerful activity against wear resulting in strongly reduced wear of piston-rings and cylinder-liners

**Application:**

This universal lubricating oil is suitable for gasoline or diesel engines, with or without super-charging. This motor oil is suitable for application in mixed fleets.

**Performance Level:**

ACEA E7  
API CH-4/SJ  
Cat ECF-1-a  
Cummins CES 20076/20077  
Deutz DQC III-10  
MAN M 3275-1  
MB 228.1  
MTU Type 2  
Volvo VDS-2

**Typicals:**

Density at 15 °C, kg/l: 0,884  
Viscosity -20 °C, mPa.s: 5700  
Viscosity 40 °C, mm<sup>2</sup>/s: 107,00  
Viscosity 100 °C, mm<sup>2</sup>/s: 14,50  
Viscosity Index: 140  
Flash Point COC, °C: 220  
Pour Point, °C: -33  
Total Base Number, mgKOH/g: 11,1  
Sulphate Ash, %: 1,43

**Packaging:**

litres	packing		per box	per pallet
20	canister	-		24
208	barrel	-		4
1000	pallet tank	-		1

\*CP pallet size 114 x 114 cm.