



## ARIAL UTTO SYNTHETIC NF



This special synthetic UTTO has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment.

---

**SKU:** 201020

**Categories:** [Многофункциональные масла \(UTTO\)](#)

## PRODUCT DESCRIPTION

A modern synthetic UTTO formulated with a balanced mix of synthetic components and additives to obtain the following properties:

- a high and stable viscosity index
- a low pour point
- a very good stability against oxidation
- good extreme pressure- and anti-wear properties
- optimal friction properties and therefor applicable in systems with "wet" brakes
- excellent corrosion and foam preventing properties
- prevention of the so-called "stick-slip"

### Application:

This special synthetic UTTO has been developed for the hydraulics and transmissions of most generally used agricultural and road-construction equipment.

### Performance Level:

API GL-4  
Allison C4  
Case MS1207/MS1209  
Cat TO-2

John Deere J20A  
Massey Ferguson M1141/M1143/M1145  
Volvo WB 102  
ZF TE-ML 03E/05F

**Typicals:**

Density at 15 °C, kg/l: 0,852  
Viscosity 40 °C, mm<sup>2</sup>/s: 38,00  
Viscosity 100 °C, mm<sup>2</sup>/s: 7,63  
Viscosity Index: 175  
Flash Point COC, °C: 232  
Pour Point, °C: -42

**Packaging:**

litres	packing		per box	per pallet
20	canister	-		24
60	barrel	-		9
208	barrel	-		4
1000	pallet tank	-		1

\*CP pallet size 114 x 114 cm.